

Darcel

THE ART OF STYLE

Fitting Instructions
Cleaning Instructions

FITTING INSTRUCTIONS FOR ROUND ROSE LEVER FURNITURE

- Mark out the centre hole for your spindle to sit through. Drill through door with a 20mm drill bit.
- Place spindle through hole in door and place back plates square and evenly either side of door.
- Mark all screw holes with a bradawl.
- Remove backplates and spindle bar.
- Drill pilot holes for the wood screws to be inserted on all bradawl marks using 2mm drill bit.
- Re-attach the spindle through door lock/latch and attach backplates to door using screws supplied.
- Tighten all grub screws to secure the spindle to door using alan key provided.

Cleaning Instructions

Always use soft cloth. If necessary, you can dampen the soft cloth. If required, you can use a PH neutral soap with a soft cloth for stubborn areas, but this should be cleaned off immediately after application with a soft damp cloth.

Under no circumstances should a hard tool (brush or wire wool), or an abrasive or acidic substance be used on the door handles.

Special Warning on Corrosive Air

Please be aware that environments where there are high concentrations of chemicals in the air, for example vapours from low quality paint or corrosive agents, corrosion and damage may occur to the surface of the door lever. Door levers should not be fitted into such environments until the high concentrations of chemicals in the air have dispersed.

Darcel
THE ART OF STYLE

www.darcelhandles.co.uk